COUNTERMAX MX-L-120-LO I UNDERCABINET

89901 / 89902 / 89903 / 89904


- 40,000 rated life hours
- Linkable end-to-end or with MX Interlink5
- Value pricing
- Frosted Lens
- CRI 80+
- Suitable for Dry location
- ETL cETL





PRODUCT DESCRIPTION

The MX-L120-LO is our economy LED Under counter. It features an extruded aluminum body with anodized finishes and a frosted acrylic lens. Its easy mount end caps makes for easy and quick installation without the use of clips. Can be direct wired with the use of direct wire box or plugged directly into outlet.



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT
89901	10"L x 2"W x 1"H	0.26 lb
89902	21"L x 2"W x 1"H	0.40 lb
89903	30"L x 2"W x 1"H	0.62 lb
89904	40"L x 2"W x 1"H	0.77 lb

LAMPING

			COLOR				
MODEL BULB TYPE		TEMP.	LUMENS	CRI	INPUT	DIMMABLE	
	89901	(1) 6W PCB LED (Integrated)	3000K	390	+08	120V	No
	89902	(1) 10W PCB LED (Integrated)	3000K	650	+08	120V	No
	89903	(1) 12W PCB LED (Integrated)	3000K	780	+08	120V	No
	89904	(1) 14W PCB LED (Integrated)	3000K	910	+08	120V	No

ACCESSORIES



89958 BK, **WT**MXInterLink5 Direct Wire Box 6.5"L x 2.75"W x 1"H



53255Plastic Wire Clips
(Package of 10)
1"L x 0.5"W x 0.25"H



MXInterLink4 Connector Cord 9" **89951** BK, **WT** 18" **89952** BK, **WT** 24" **89953** BK, **WT**



89954 BK, WT MXInterLink5 Connector Cord 72"

• Includes on/off switch

FINISHES OPTIONS:

White (WT)

Anodized Bronze (BRZ)

MATERIAL:

Aluminum + Acrylic

AVAILABLE SIZE:

10" | 21" | 30" | 40"

INCLUDES

Two captured mounting screws

RATINGS:

ETL cETL DRY Location



5

ADDITIONAL:

RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | **F**. 626.956.4225 | maximlighting.com