## TRIM | FLUSH MOUNT

### 57670/57880/57881/57882/57883/57884/57885/57894/57895

- Die Cast Aluminum
- $\bullet\,$  Size options between 5", 7" , 9", 11" and 16"
- Ultra-thin ½" height with less than ¼" trim
- Available in 3000k (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Black (BK), Polished Chrome (PC) and Satin Nickel (SN)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box (pancake and mud ring acceptable)
- Pendant light accessory available (sold separately)
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65








57600 PENDANT ACCESORY

(Sold Separately, Fixture NOT included)

#### PRODUCT DESCRIPTION

Thin discs of evenly illuminated LED create the impression of recessed lighting. The die-cast aluminum housings are available in White, Black, Satin Nickel, and Polished Chrome all with a thoughtfully recessed White polycarbonate diffuser. High efficiency and good color rendering make this a perfect choice for your next project. Use the optional pendant adapter to convert any size to a hanging fixture.



MEASUREMENTS		LAMPING		COLOR		
MODEL DIMENSION	CRI	MODEL	. BULB TYPE	TEMPERATURE	INPUT	DIMMABLE
57670 16"L x 16" W x 1.5"H	90+	57670	25W LED (Integrated)	3000K	120V	0-10V
57880 5"L x 5" W x 0.5"H	90+	57880	12.5W LED (Integrated)	3000K	120V	0-10V
57881 5"L x 5" W x 0.5"H	90+	57881	12.5W LED (Integrated)	4000K	120V	0-10V
57882 7"L x 7" W x 0.5"H	90+	57882	15W LED (Integrated)	3000K	120V	0-10V
57883 7"L x 7" W x 0.5"H	90+	57883	15W LED (Integrated)	4000K	120V	0-10V
57884 9"L x 9" W x 0.5"H	90+	57884	18W LED (Integrated)	3000K	120V	0-10V

57885 18W LED (Integrated)

57894 15W LED (Integrated)

15W LED (Integrated)

**WIRE LENGTH** 8"L 57600 2.25"W x 10.75"H x 2.25"L, 120"OAH 120"L

57895

90+

90+

90+

#### **FINISHES OPTION**

	Black
腦	Satin Nicke
	White

#### GLASS

White WT

#### MATERIAL

PC + Aluminum

RATINGS cELusWet Location Energy Star JA8 Listed





# **AVAILABLE SIZE:** 5" | 7" | 9" | 16"

5 | / | 9 | 16

#### ADDITIONAL

RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



57885 9"L x 9" W x 0.5"H

57894 7"L x 7" W x 0.5"H

57895 7"L x 7" W x 0.5"H

WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

0-10V

0-10V

0-10V

120V

120V

#### EASTERN DISTRIBUTION CENTER

4000K

3000K

4000K

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com